


1055



DAUERHAFTE VERBINDUNGEN.

Rundprofil Hitzebeständig

Non-flammable fiberglass-based backfill cord



Technical data sheet

Version: 12-2023

1. Properties

The 1055 Rundprofil Hitzebeständig is a non-flammable backfill cord, based on fiberglass. It can be used as sealing-cord, for glazing and also for fire protection and heat-areas up to 550° C. For usage in indoor- and outdoor.

2. Dimensions

Diameter	6mm	8mm	10mm	12mm	15mm
Artno.	8320006	8320008	8320010	8320012	8320015
lm/roll	100	100	100	100	100

3. Application

Before installation the sealing cord any contamination or dirt in the joint must be completely and thoroughly removed. The sides of the joints must be cleaned using suitable tools. After the joint has been completely cleaned, the cord must be inserted and compacted at the desired installation location. When installing two layers directly on top of each other, the first layer must be compacted before the second layer is installed. The cord must be cut of with an overlength of approx. 10mm. If jointing with a suitable sealant the technical data sheets and safety data sheets of the products used must be strictly observed. Any building authority or fire safety regulations must be observed. **Attention:** Before any cutting to length, the cord must be wrapped with an approx. 50 to 60 mm wide adhesive tape at the cutting line in order to avoid the profile falling apart! In addition, the cord must always be unrolled from the outside to the inside of the roll. When unrolling in the opposite direction, i.e. from the inside out, there is a risk that the cord will become "twisted", become intertwined and being damaged.

4. Liability for defects

The information, in particular the suggestions for the processing and use of our products, is based on our knowledge and experience in normal use cases at the time of printing. Depending on the specific circumstances, in particular with regard to substrates, processing and environmental conditions, the results may differ from this information. Therefore the guarantee of a work result or a liability, for whatever legal reasons, can be justified neither from these references, nor from a verbal consultation, unless we are guilty of intent or gross negligence in this respect. Ramsauer guarantees that its products comply with the technical properties specified in the technical data sheets until the expiry date.

Product users must consult the latest technical data sheet, which can be requested from us. Our current General Terms and Conditions apply, which you can download at any time from our homepage at **www.ramsauer.eu**. On publication of a new version/revision of the technical data sheet, all previous versions of the respective product lose their validity.